

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/06/2005

Reviewed on 05/06/2005

1 Identification of substance

Trade name: MRO ASA 61 GRAY
Product code: 0006201416
Manufacturer/Supplier: SEYMOUR OF SYCAMORE
 917 Crosby Avenue
 Sycamore, IL 60178
 (815)-895-9101, www.seymourpaint.com

Information department: Health & Safety Department
Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S.



2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	acetone	Xi, F; R 11-36-66-67	18.03%
74-98-6	propane	F+; R 12	15.82%
106-97-8	n-butane	F+; R 12	9.29%
1317-65-3	Calcium Carbonate	Xi; R 36/37/38	8.26%
13463-67-7	titanium dioxide	Xi; R 37	7.3%
2807-30-9	Glycol Ether EP	Xn; R 21-36	4.87%
108-10-1	methyl isobutyl ketone	Xn, F; R 11-20-36/37-66	4.57%
110-19-0	isobutyl acetate	F; R 11-66	3.63%
107-87-9	Methyl Propyl Ketone	F; R 11	2.95%
1330-20-7	xylene (mix)	Xn; R 10-20/21-38	2.42%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description: Irritant
Extremely flammable

Physical dangers: Has a narcotizing effect.
 Danger! Extremely flammable liquid and vapor in a pressurized container. Vapors may cause flash fire.
 Keep away from heat, sparks, and flame.
 R 12 Extremely flammable.
 R 36/37 Irritating to eyes and respiratory system.
 R 67 Vapours may cause drowsiness and dizziness
 Keep out of the reach of children.

Effects of short-term overexposure: Vapors cause irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4): Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (scale 0 - 4): Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 2)
 USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/06/2005

Reviewed on 05/06/2005

Trade name: MRO ASA 61 GRAY

Protective equipment: No special measures required.

(Contd. of page 1)

6 Accidental release measures

Personal safety

Precautions:

Wear protective equipment. Keep unprotected persons away.

Environmental safety

Precautions:

Do not allow product to reach sewage systems or ground water.
Inform appropriate authorities in case of seepage into water course or sewage system.

Measures for cleaning/ collecting:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material.

Do not smoke. Protect from electrostatic charges.

Storage requirements:

Observe pressurized container storage regulations. Consult with your local authorities.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL 2400 mg/m³, 1000 ppm
REL 590 mg/m³, 250 ppm
TLV Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 1188 mg/m³, 500 ppm
BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
REL 1800 mg/m³, 1000 ppm
TLV (4508) mg/m³, (2500) ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
TLV 1900 mg/m³, 800 ppm

1317-65-3 Calcium Carbonate

PEL 15*; 5** mg/m³
*Total dust **Respirable fraction
REL 10*; 5** mg/m³
*Total dust **Respirable fraction
TLV 10 mg/m³
(e)

108-10-1 methyl isobutyl ketone

PEL 410 mg/m³, 100 ppm
REL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm
TLV Short-term value: 307 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm
BEI

110-19-0 isobutyl acetate

PEL 700 mg/m³, 150 ppm
REL 700 mg/m³, 150 ppm
TLV 713 mg/m³, 150 ppm

107-87-9 Methyl Propyl Ketone

PEL 700 mg/m³, 200 ppm
REL 530 mg/m³, 150 ppm
TLV Short-term value: 881 mg/m³, 250 ppm
Long-term value: 705 mg/m³, 200 ppm

(Contd. on page 3)
USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/06/2005

Reviewed on 05/06/2005

Trade name: MRO ASA 61 GRAY

(Contd. of page 2)

1330-20-7 xylene (mix)

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

Protective hygienic measures:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure. Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties:**General Information:**

Form:	Aerosol
Color:	According to trade name description in section 1.
Odor:	Solvent
Boiling point/Boiling range:	-44°C (-47°F)
Flash point:	-19°C (-2°F)
Ignition temperature:	365.0°C (689°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	13.0 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	466.4 g/l / 3.89 lb/gl
VOC in weight percent (less acetone):	46.6 %
Solids content:	35.3 %

10 Stability and reactivity:**Conditions to be avoided:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.**Possibility of Hazardous****Reactions:** No dangerous reactions known.**11 Toxicological information:****Primary effect on the skin:** No irritant effect.**Primary effect on the eye:** Irritating effect.**Sensitization:** No sensitizing effects known.**12 Ecological information****Other information:** This product does not contain any chloroflouorocarbons (CFC's),chlorinated solvents, or lead. No specific ecological data is available for this product.**13 Disposal considerations****DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

(Contd. on page 4)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 05/06/2005

Reviewed on 05/06/2005

Trade name: MRO ASA 61 GRAY**Recommendation:** Empty cans should be recycled.

(Contd. of page 3)

14 Transport information:

Hazard class: 2.1
Identification number: N/A
Label: 2.1
ADR/RID class: 2 5TF Gases
UN-Number: 1950
IMDG Class: 2
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No
ICAO/IATA Class: 2.1
Proper shipping name: Aerosols, Flammable
 Consumer Commodity ORM-D

15 Regulations**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1	methyl isobutyl ketone
1330-20-7	xylene (mix)

TSCA (Toxic Substances**Control Act):** All ingredients are listed.**PROPOSITION 65 Chemicals known to cause cancer:**

100-41-4 ethyl benzene

PROPOSITION 65 Chemicals known to cause reproductive toxicity:

None of the ingredients in this product are listed.

Canadian WHMIS:

Class A, B5---Flammable Aerosols

EPA:

A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1	acetone	D
110-19-0	isobutyl acetate	D
1330-20-7	xylene (mix)	D

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
 Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

13463-67-7	titanium dioxide	3
1330-20-7	xylene (mix)	3

ACGIH TLVs:

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
110-19-0	isobutyl acetate	A4
1330-20-7	xylene (mix)	A4

NIOSH:

13463-67-7	titanium dioxide
1333-86-4	Carbon black

(Contd. on page 5)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 05/06/2005

Reviewed on 05/06/2005

Trade name: MRO ASA 61 GRAY

(Contd. of page 4)

**USDA (United States
Department of
Agriculture):**

This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Craig Swafford, Regulatory Affairs. Email: cswafford@seymourpaint.com

USA