MSDS Document

Product Dynatex® 52125 Penetrating Oil

1. Chemical Product and Company Identification

Trade Name of this Product Dynatex® 52125 Penetrating Oil MSDS ID DYN52125

Manufacturer


Accumetric, LLC 350 Ring Road

Elizabethtown, KY 42701

Phone Number (270) 769-3385 **Emergency Phone**

CHEMTREC (800) 424-9300 Revision Date 11/4/2005





2. Composition and Information on Ingredients

CAS Number Ingredient Weight % **ACGIH TLV PEL** STEL Carbon dioxide 124-38-9 5000 ppm 5000 ppm

Distillates, petroleum,

64742-47-8

hydrotreated light

3. Hazard Identification

Eve Contact

Direct spray or vapors will irritate and may harm eyes.

Skin Contact

May cause skin irritation.

Inhalation

High concentrations of vapors may irritate nose and throat and cause symptoms of intoxication such as dizziness, nausea, headache or indigestion.

Ingestion

Swallowing may cause abdominal irritation, nausea, vomiting and diarrhea.

Page 2 6 Print Rev. Date 11/07/2005 MSDS ID DYN52125 Dynatex® 52125 Penetrating Oil

Existing Conditions Aggravated by Exposure

Pre-existing lungs disorders

Important

Extremely flammable. Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122F/50C (ex: electric lights). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. DO NOT SMOKE WHILE USING THIS PRODUCT.

4. First Aid Information

Eve Contact

Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation develops.

Skin Contact

Remove from skin and wash throughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.

Inhalation

Remove individual to fresh air. Give oxygen if breathing is labored. If breathing has stopped give artificial respiration. Keep person warm, quiet and seek medical attention.

Ingestion

DO NOT INDUCE VOMITING. Seek immediate medical attention.

5. Fire Fighting Measures

Extinguishing Media

Carbon Dioxide, Dry Chemical, Foam

Unusual Fire and Explosion Hazards

Contents under pressure. Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. Do not use near fire, sparks or flame. Do not puncture or incinerate container. Do not expose to temperatures exceeding 120F as containers may vent, rupture or burst.

Special Fire Fighting Procedures

Full protective equipment including self-contained breathing apparatus should be use. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to keep cool closed containers to prevent build-up and possible auto-ignition or explosion when exposed to extreme heat.. Use proper equipment to protect personnel form bursting containers.

6. Accidental Release Measures

Steps to be taken in case of spill or release

Absorb spill with inert material then place in a chemical waste container. Dispose of spill

Page 3 6 Print Rev. Date 11/07/2005 MSDS ID DYN52125 Dynatex® 52125 Penetrating Oil

material in accordance with regulations.

7. Handling and Storage

Handling

Do not puncture or incinerate containers. Keep out of reach of children. Read label precautions carefully. Follow label directions to avoid injury. Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

Storage

Do not store at temperatures above 120F. Do not puncture or incinerate containers. Keep out of reach of children. Store in accordance with NFPA 30B for Level 3 Aerosols.

Important

Extremely flammable. Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122F/50C (ex: electric lights). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. DO NOT SMOKE WHILE USING THIS PRODUCT.

8. Exposure Controls and Personal Protection

Precautionary Measures

Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

Eve Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

Ventilation

Local exhaust preferable. General exhaust acceptable if exposure is below applicable exposure limits.

Respiratory Protection

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

Other Precautions

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

Page 4 6 Print Rev. Date 11/07/2005 MSDS ID DYN52125 Dynatex® 52125 Penetrating Oil

9. Physical and Chemical Properties

Physical State Aerosol liquid

Specific Gravity 0.7

Color/Appearance Amber to brown, clear
Odor Mild sulfonate odor
pH Not applicable
Boiling/Cond. Point > 300F

Solubility Insoluble in water
Evaporation Rate Less than BuAc
VOC % 45.0%

Vapor Pressure Not established

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability

Stable

Hazardous Polymerization

Will not occur

Conditions to Avoid

Open flames; Tempertures above 120F

Materials to Avoid

Avoid contact with strong oxidizers.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide, hydrocarbons

11. Toxicological Information

Chronic Hazards

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Carcinogenicity

This product contains Methylene Diphenyl Isocyanate (MDI). MDI is not listed by the NTP, IARC or regulated by OSHA as a carcinogen. However, it has been shown to alter cells in certain experiments. Although inconclusive, these cellular changes are thought to indicate potential carcinogenicity.

12. Ecological Information

Environmental Fate and Distribution

Complete information is not yet available.

Page 5 6 Print Rev. Date 11/07/2005 MSDS ID DYN52125 Dynatex® 52125 Penetrating Oil

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14. Transportation Information

DOT Road Shipment Information

DOT Classification: HAZARDOUS

DOT Description: Consumer Commodity ORM-D

UN Number: UN1950 Hazard Class: 2.1 Packing Group: N/A

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA Title III Section 302 Extremely Hazardous Substances

None

SARA Title III Section 304 CERCLA Hazardous Substances

None

SARA Title III Section 313 Toxic Chemicals

None present or none present in regulated quantities.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to

Page 6 6 Print Rev. Date 11/07/2005 MSDS ID DYN52125 Dynatex® 52125 Penetrating Oil

cause cancer, birth defects or other reproductive harm: None known

New Jersey

Carbon dioxide (124-38-9)

Pennsylvania

Carbon dioxide (124-38-9)

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.