# **MSDS** Document

# Product Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade

# 1. Chemical Product and Company Identification

# Trade Name of this Product Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade MSDS ID DY49285

Manufacturer

Accumetric, LLC 350 Ring Road Elizabethtown, KY 42701 
 Phone Number

 (270) 769-3385

 Emergency Phone

 (800) 928-2677

 Revision Date
 9/24/2004



# 2. Composition and Information on Ingredients

<b>Ingredient</b>	CAS Number	<b>Weight %</b>	<b>ACGIH TLV</b>	<b>PEL</b>	<b>STEL</b>
Ethyltriacetoxysilane	17689-77-9	1% - 5%	TWA 10ppm	TWA 10ppm	15ppm
Methyltriacetoxysilane	4253-34-3	1% - 5%	TWA 10ppm	TWA 10ppm	15ppm

# 3. Hazard Identification

#### **Primary Routes of Entry**

Eye contact, inhalation, skin contact

#### Eye Contact

Direct contact may cause moderate irritation.

### Skin Contact

May cause moderate irritation.

#### Inhalation

Irritates respiratory passages very slightly.

#### Ingestion

No significant effects expected from a single short term exposure.

Page 2 6 Print Rev. Date 09/24/2004 MSDS ID DY49285 Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade

Symptoms of Overexposure

No known applicable information.

Existing Conditions Aggravated by Exposure None known.

# 4. First Aid Information

#### Eye Contact

Immediately flush with water for 15 minutes. Seek medical attention.

#### **Skin Contact**

Remove from skin and wash throughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.

#### Inhalation

No first aid should be needed.

#### Ingestion

No first aid should be needed.

#### Comments

Treat according to person's condition and specifics of exposure.

# 5. Fire Fighting Measures

**Flash Point** 

Not Applicable

Auto-ignition Temperature Not determined

Flammability Limits in Air Not determined

#### **Extinguishing Media**

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

#### **Fire Fighting Measures**

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire or Explosion Hazards None

Hazardous Decomposition Products Thermal breakdown of this product during fire or very high heat conditions may evolve the

Page 3 6 Print Rev. Date 09/24/2004 MSDS ID DY49285 Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade

following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds Formaldehyde Hydrogen Silicon dioxide Metal oxides

# 6. Accidental Release Measures

#### Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases.

# 7. Handling and Storage

#### Handling

Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact.

#### Storage

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

# 8. Exposure Controls and Personal Protection

#### **Exposure Controls**

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

#### **Eye Protection**

Safety goggles or glasses with side shields are recommended.

#### **Skin Protection**

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and throughly cleaned before reuse. Chemical protective gloves are recommended.

Page 4 6 Print Rev. Date 09/24/2004 MSDS ID DY49285 Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade

#### **Respiratory Protection**

No respiratory protection should be needed with good local ventilation.

#### **Precautionary Measures**

Avoid eye contact. Avoid skin contact. Use reasonable care.

#### Comment

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.

#### Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

# 9. Physical and Chemical Properties

Physical State	Paste
Specific Gravity	1.032
Color/Appearance	White
Odor	Acetic Acid Odor
рН	Not Determined
Boiling/Cond. Point	Not Determined
Melting/Freezing Point	Not Determined
Solubility	Not Determined
Evaporation Rate	Not Determined
Viscosity	Not Determined
Vapor Density	Not Determined
Vapor Pressure	Not Determined

#### Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

#### 10. Stability and Reactivity

Chemical Stability Stable

Hazardous Polymerization Will not occur

Conditions to Avoid None

#### Materials to Avoid / Incompatibility

Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form.

#### **11. Toxicological Information**

#### **Component Toxicology Information**

No known applicable information.

Page 5 6 Print Rev. Date 09/24/2004 MSDS ID DY49285 Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade

#### Special Hazard Information on Components

No known applicable information.

# 12. Ecological Information

**Environmental Fate and Distribution** Complete information is not yet available.

#### **Environmental Effects**

Complete information is not yet available.

#### Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

# 13. Disposal Considerations

#### Waste Disposal Method

Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations. Not a RCRA hazardous waste.

# 14. Transportation Information

**DOT Road Shipment Information (49 CFR 172.101)** Not subject to DOT.

#### **Ocean Shipment (IMDG)**

Not subject to IMDG code.

#### Air Shipment (IATA)

Not subject to IATA regulations.

# **15. Regulatory Information**

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### **TSCA Status**

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Title III Section 304 CERCLA Hazardous Substances None

Page 6 6 Print Rev. Date 09/24/2004 MSDS ID DY49285 Dynatex® 49285 White RTV Silicone Sealant - Industrial Grade

#### SARA Title III Section 312 Hazard Class

Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No

#### SARA Title III Section 313 Toxic Chemicals

Alumina hydrate (21645-51-2)

#### California

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

#### Massachusetts

Alumina hydrate (21645-51-2) Silica, amorphous (7631-86-9) Titanium dioxide (13463-67-7)

#### **New Jersey**

Alumina hydrate (21645-51-2) Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ethyltriacetoxysilane (17689-77-9) Methyltriacetoxysilane (4253-34-3) Silica, amorphous (7631-86-9) Titanium dioxide (13463-67-7)

#### Pennsylvania

Alumina hydrate (21645-51-2) Dimethyl siloxane, hydroxy-terminated (70131-67-8) Silica, amorphous (7631-86-9) Titanium dioxide (13463-67-7)

# **16. Other Information**

#### Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.